



Superior Solutions



STRIP OFF

Methylene chloride-free aerosol paint remover

- Removes all types of paint, coatings, fillers and remnants on surfaces, which are resistant to solvents without risk to health.
- Free of chlorinated solvents.
- Very high active substance content (> 85 %).
- For use indoors and outdoors.
- Deep removal of paints (acrylic, vinyl, glycerol, antifouling) and coatings.
- Dissolves residual plastics which may debase plastic-making moulds.
- Removal of the filling of joints.
- Quick removal of graffiti.
- Can be used on vehicle bodies, grilles, doors and gates, on the floor and walls, on moulds in the plastic-making industry.
- Incombustible.

APPLICATION

STRIP OFF is a powerful blend of chemicals formulated to remove aerosol spray paints (including cellulose paint), felt pen and ball point inks, crayon, grease and lipstick from all hard surfaces including metal, concrete, brickwork, ceramics, quarry tiles, porcelain, wood, vitreous enamel and fibreglass.

USAGE

Shake the aerosol can before use. Scrape the paint on the base before application of the aerosol spray to increase penetration. Spray the treated area from a distance of about 20 cm. Leave to act for 10 - 15 minutes (according to the thickness of the coat or cement or filling to be removed) until the agent dries (penetration of the active substance and evaporation of the solvents). Blisters indicate the efficiency of the agent. Use a scraper and remove the entire paint coat or remains. To remove coats, you may use a dry rag, scraper or metallic brush. Rinse with water.

CONDITIONS FOR USE

It is essential to do a trial on polyethylene, polypropylene and polyester. Do not apply to PVC, polystyrene, organic glass and rubber. It is recommended to use protective gloves and goggles. Abide by the instructions on the pack.

CHARACTERISTICS

Propellant: propane/butane
Net volume: 600 ml.
Odour: typical

All information in this document is based on our practical experience and/or laboratory tests. Due to the large spectrum of circumstances for usage and unpredictable human factors, we recommend that you always test our products before final usage. This technical data sheet has perhaps already been revised based on legislation, availability of the individual ingredients or newly acquired information. We can send you upon request the latest valid version, which is the sole valid version.

Version 8543-0413