

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **WOOD DOCTOR UV**

· Article number: 96930001

· UFI: RKH0-M0R1-400D-AY21

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· Life cycle stages PW Widespread use by professional workers

· Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC15 Non-metal-surface treatment products

· Application of the substance / the mixture Maintenance product

· **1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier:

ZEP ITALIA SRL

Piazzale Luigi Cadorna, 2

20123 Milano (MI) - Italy;

Via Nettunense Km. 25.000

04011 Aprilia (LT) - Italy

T: +39.06.926691

F: +39.06.92747061

@: tecnico@zepuurope.com

Sito: www.zep.it

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax: (NL) + 31 164 266 710 (B) + 32 2 347 1395

@: info@zepbenelux.com

Distributed in the UK by:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

· **Further information obtainable from:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **1.4 Emergency telephone number:**

NHS +44 0845 46 47 (England or Wales); +44 08454 24 24 24 (Scotland)

emergency number (europe): 112

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **2.2 Label elements**

· Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard-determining components of labelling:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Hydrocarbons, terpene processing by-products. May produce an allergic reaction.

· **2.3 Other hazards** The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H336 EUH066	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane (< 0.1% butadine) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane (<0.1% butadine) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	1-2.5%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	0.1-1%
CAS: 68956-56-9 EINECS: 273-309-3 Reg.nr.: 01-2119980606-28-xxxx	Hydrocarbons, terpene processing by-products ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

EU

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

EU

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 34590-94-8 (2-methoxymethylethoxy)propanol

IOELV Long-term value: 308 mg/m³, 50 ppm
Skin

· DNELs

CAS: 34590-94-8 (2-methoxymethylethoxy)propanol

Oral	DNEL Long term-systemic	1.67 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	15 mg/kg human/day (consumer)
		65 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	37.2 mg/m ³ (consumer)
		310 mg/m ³ (worker)

CAS: 68956-56-9 Hydrocarbons, terpene processing by-products

Oral	DNEL Long term-systemic	0.3 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	0.3 mg/kg human/day (consumer)
		0.8 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	0.7 mg/m ³ (consumer)
		2.9 mg/m ³ (worker)

· PNECs

CAS: 34590-94-8 (2-methoxymethylethoxy)propanol

PNEC Freshwater mg/L	19 mg/L
PNEC Marinewater mg/L	1.9 mg/L
PNEC Freshwater sediment	70.2 mg/Kg
PNEC Marine water sediment	7.02 mg/Kg
PNEC Intermittent release	190
PNEC Soil	2.74 mg/Kg
PNEC Sewage treatment Plant mg/L	4,168 mg/L

CAS: 68956-56-9 Hydrocarbons, terpene processing by-products

PNEC Freshwater µg/L	21 µg/L (-)
PNEC Marinewater µg/L	0.21 µg/L (-)
PNEC Intermittent release	21 /µg/L (-)
PNEC Soil	110 mg/Kg (-)
PNEC Sewage treatment Plant mg/L	6.4 mg/L (-)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· **Hand protection**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.5 mm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Light yellow

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

41 °C

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

0.6 Vol %

· **Upper:**

7 Vol %

· **Flash point:**

-19 °C

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Insoluble.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

2.5 hPa

· **Density and/or relative density**

· **Density at 20 °C:**

0.77863 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Aerosol

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:**

240 °C

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Solvent content:**

· **Organic solvents:**

72.2 %

· **EU-VOC:**

688.3 g/l

· **EU-VOC**

88.40 %

· **Swiss VOC:**

88.40 %

· **Solids content:**

29.7 %

· **Change in condition**

· **Evaporation rate**

Not applicable.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**

Extremely flammable aerosol. Pressurised container: May burst if heated.

· **Oxidising gases**

Void

· **Gases under pressure**

Void

· **Flammable liquids**

Void

· **Flammable solids**

Void

· **Self-reactive substances and mixtures**

Void

· **Pyrophoric liquids**

Void

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 5)

· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50 / 4 h	>4,951 mg/l (Rat)

CAS: 34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	>4,000 mg/kg (Rat)
Dermal	LD50	9,510 mg/kg (Rabbit)
	LC50 / 48 h	1.919 mg/ltr (Daphnia magna (water flea))

CAS: 68956-56-9 Hydrocarbons, terpene processing by-products

Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 34590-94-8 (2-methoxymethylethoxy)propanol

LC50 / 96 h	>10,000 mg/ltr (Pimephales promelas)
-------------	--------------------------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 6)

EC 50 / 72 H 1,000 (Selenastrum capricornutum (Algae))

CAS: 68956-56-9 Hydrocarbons, terpene processing by-products

LC50 / 96 h 5.07 mg/ltr (fish)

EC 50 / 48 h 2.1 mg/ltr (Daphnia magna (water flea))

EC 50 / 72 H 3.08 /mg/L (Selenastrum capricornutum (Algae))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
- The material is harmful to the environment.
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations

- **European waste catalogue**

15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
----------	--

15 01 00	packaging (including separately collected municipal packaging waste)
----------	--

15 01 04	metallic packaging
----------	--------------------

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
----------	---

20 01 00	separately collected fractions (except 15 01)
----------	---

20 01 13*	solvents
-----------	----------

HP3	Flammable
-----	-----------

HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
-----	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal in accordance with administrative provisions

SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA** UN1950

- **14.2 UN proper shipping name**

- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 7)

· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 2020/878 annex II of REACH;

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.· **Hazard pictograms**

GHS02

GHS07

· **Signal word** Danger

(Contd. on page 9)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 8)

· **Hazard-determining components of labelling:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category** P3a FLAMMABLE AEROSOLS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	88.4

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008** Calculation method

· **Department issuing SDS:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2022

Version: 2 (replaces version 1)

Revision: 18.02.2022

Trade name: **WOOD DOCTOR UV**

(Contd. of page 9)

· **Contact:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **Date of previous version:** 12.01.2022· **Version number of previous version:** 1· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

WELL: The highest acceptable concentration

IOELV: Indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**